

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B01L 3/00</b>		<b>A3</b>	(11) International Publication Number: <b>WO 98/08606</b>
			(43) International Publication Date: 5 March 1998 (05.03.98)
(21) International Application Number: <b>PCT/US97/14939</b>		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 25 August 1997 (25.08.97)		<b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(30) Priority Data: 08/704,804      26 August 1996 (26.08.96)      US			
(71) Applicant: BIOSITE DIAGNOSTICS INCORPORATED [US/US]; Suite D, 11030 Roselle Street, San Diego, CA 92121 (US).			
(72) Inventors: BUECHLER, Kenneth, Francis; 12523 Manifesto Place, San Diego, CA 92130 (US). BATT, Richard, Roger; 1646 Davis Street #18, San Jose, CA 95126 (US).			
(74) Agents: LITHGOW, Timothy, J. et al.; Lyon & Lyon LLP, Suite 4700, 633 West Fifth Street, Los Angeles, CA 90071-2066 (US).		(88) Date of publication of the international search report: 16 July 1998 (16.07.98)	

(54) Title: DEVICES INCORPORATING FILTERS FOR FILTERING FLUID SAMPLES

## (57) Abstract

Devices and use thereof, the device comprising a filter and a means for region specific compression of the filter. Alternatively, the device comprises a filter; a region containing the filter; a fluid access port to the region containing the filter; a fluid egress port from the region containing the filter; and a lateral fluid flow path through the filter connecting the fluid access port to the fluid egress port. Alternatively, a single stop assay device whereby fluid movement through the device occurs substantially solely due to action of capillary force, the device comprising a filter; a region containing the filter; a fluid access port to the region containing the filter; a means for retarding movement of particles through a peripheral filter surface; a fluid egress port from the region containing the filter; a lateral fluid flow path through the filter connecting the fluid access port to the fluid egress port, whereby sample fluid substantially devoid of particulate matter is released from the filter through the egress port, and, an exit region fluidly connected to the egress port. Use of the device optionally comprises means for producing an assay result in an exit region of the device.

